LIFTING BAGS



Lifting Bags ZP

Туре		ZP 3	ZP 6	ZP 10	ZP 20	ZP 30
Part - No.		1801	1802	1803	1804	1805
Lifting capacity	kN	30	60	100	200	300
Lifting height	mm	120	160	210	300	350
Dimensions	mm	230 x 230	300 x 300	390 x 390	530 x 530	640 x 640
Insertion height	mm	27	27	27	27	27
Air requirement at 8 bar	I	16	38	90	250	470
Operating pressure	bar	8,0	8,0	8,0	8,0	8,0
Test pressure	bar	12,0	12,0	12,0	12,0	12,0
Burst pressure	bar	75,0	64,0	57,0	45,0	36,0
Weight	kg	1,5	2,4	4,3	7,6	11,2

Accessories

Part-No. Description

2001	Inflation hose with quick
	couplings, 3 m

2014	Inflation hose with quick coupling and nippel, 5 m
2015	Inflation hose with quick coupling and nippel, 10 m

2028	Safety and control gauge
	8 bar–ZP 8

2029	Double safety and control gauge
	8 bar–2 ZP 8



These bags made of top-quality rubber and the Kevlar fibres enable rescuers to lift and remove heavy loads in various natural disasters, to pull people out of damaged vehicles in car or train accidents etc. The bags are also very useful in assembling heavy machines, tire changing in all kinds of vehicles and they are extraordinarily advantageous in assembling, repairing and maintaining water supply lines, water mains, gas lines and oil pipelines. The lifting bags can also be used for splitting stone blocks and pushing them away and they can be found very useful at airports, in the army etc. The standard set consists of five different models the lifting force of which is 3 to 30 metric tons.



Part-No. Description

2005 Pressure reducer 200/8 bar



